



PNEUMATIC PRODUCTS

- V aried Applications & Gas Compatibility
- A bsolute Removal Rating
- L ow Operating Costs
- U niform, Predictable Performance
- E xtended Service Life

The high area PPC particulate filter cartridge has been designed for use as an afterfilter downstream of regenerative desiccant dryers or downstream of activated carbon bed adsorbers. All such adsorbers tend to generate small quantities of dust particles, one micrometer and larger. These abrasive contaminants erode instruments, valve seats, air cylinders, and pneumatic tools. The PPC filter can also be used prior to coalescers prolonging the life of the more costly coalescer. The PPC afterfilter, with an absolute particle rating of 0.9 micrometers, prevents these fine particles from entering the compressed air or gas stream. Stopping particles before they enter the stream means sustained system performance, longer component life, and reduced maintenance and downtime. The PPC high temperature afterfilter is designed to perform in the same manner and efficiency as the low temperature afterfilter with one difference — the media is glass fiber. This allows use of the filter downstream of heat-reactivated dryers. During this type of dryer regeneration, temperatures typically reach 450°F. Standard dryer afterfilters of epoxy coated cellulose fibers quickly deteriorate under these extreme temperatures.


SUPERIOR "CAKE VOLUME" IMPROVES ECONOMY

A key benefit of the PPC afterfilter cartridge is economy through long service — even longer than its predecessor. What extends the working life of a PPC cartridge? A design innovation in its construction which allows the medium to hold more dirt, increasing the "cake volume".

Any standard filter medium collects particles, its pores plug with debris and a loss of pressure occurs. To overcome this pressure loss, more energy must be used to operate the system or the filter must be replaced.

With a larger cake volume than standard filters, the PPC filter medium holds more particles before plugging. Its unique corrugated construction extends the on-stream life of the filter before substantial pressure loss, thereby reducing overall operating costs. Additionally the high temperature cartridge construction combines galvanized steel mesh and steel inner support core assuring reliable performance under adverse conditions and high temperatures.


Typical Contaminant Challenge to a Particulate Filter



PPC's Low and High Temperature Particulate Filters




Advantages of PPC Particulate cartridges over “molded” or “wound” cartridges using glass, cotton, wool, rayon, and other loose fiber construction.



ADVANTAGES


- Corrugated construction produces high filter area in a compact configuration. Ensures high dirt holding capacity and lower pressure drops which result in longer on-stream life, less frequent changeout, and lower operating cost.
- PPC elements will not unload or release particles because of fluctuations in flow, mechanical shock, vibration or pressure.
- Media migration (the shedding of the filter media into the system) is eliminated.



CARTRIDGE SPECIFICATIONS

Cartridge	1169621 <small>L/S</small> 2007956 <small>L/S</small>	1169622 <small>L/C</small> 2007954 <small>L/S</small> 2007953 <small>H/C</small> 2122188 <small>H/S</small>	1169623 <small>L/C</small> 2007955 <small>L/S</small> 1163823 <small>H/C</small> 1165655 <small>H/S</small>	2016905 <small>L/C</small> 2016906 <small>L/S</small> 2016908 <small>H/C</small> 2016902 <small>H/S</small>	2016910 <small>L/C</small> 2016907 <small>L/S</small> 2016903 <small>H/C</small> 2016904 <small>H/S</small>	2004352 <small>L/C</small> 2004722 <small>L/S</small> 2004354 <small>H/C</small> 2004717 <small>H/S</small>	2004353 <small>L/C</small> 2004721 <small>L/S</small> 2004355 <small>H/C</small> 2004716 <small>H/S</small>
Fluid Service	Air/Gas	Air/Gas	Air/Gas	Air/Gas	Air/Gas	Air/Gas	Air/Gas
Flow Rate ⁽¹⁾	60 scfm	100 scfm	120 scfm	200 scfm	400 scfm	600 scfm	1200 scfm
Removal Rating ⁽²⁾	0.9µm absolute	0.9µm absolute	0.9µm absolute	0.9µm absolute	0.9µm absolute	0.9µm absolute	0.9µm absolute
Clean cartridge pressure drop at rated flow and 100 psig	0.8	0.3	0.3	0.3	0.3	0.3	0.8

Materials of Construction	Low Temperature Filters:	High Temperature Filters:
• Medium	Resin impregnated cellulose	Glass fiber
• Support Core	Plated carbon steel	Plated carbon steel
• End caps	Plated carbon steel	Plated carbon steel
• Gaskets	Buna-N (60, 1001, 200, 400, 1201) Silicone (600, 1200)	Silicone



NOTE: For ordering information contact your local PPC Technical Representative.
Maximum ΔP of cartridges is 50 psid.

Typical Gases: Nitrogen, Helium, Argon. Contact PPC for filter cartridge compatibility with gases other than air.

⁽¹⁾ Recommended flow rate at 100 psig and 100°F.

⁽²⁾ Absolute filtration rating: the diameter of the largest hard spherical particle will pass through a filter under specified test conditions. This is an indication of the largest opening in the filter element. 1 µm (one micrometer) = 0.000039".

⁽³⁾ Use "HT" Filters if dryer is heat-reactivated.

Because of our policy of continuous improvement, some information, specifications and dimensions contained herein may be revised.
For confirmed accuracy, always refer to factory submittals.

SPX PNEUMATIC PRODUCTS

DISTRIBUTED BY:

4647 SW 40th Avenue
Ocala Florida 34474-5799
Tel 352-237-5500
Fax 352-873-5187
E-Mail pneumatic.products.sales@airtreatment.spx.com
Web www.pneumaticproducts.com
PIS-100i 9/03